



Traditional Water Heater

SERIE VD 50÷100



Traditional storage water heaters are the basic product range for the most varied market requirements.



- Storage tank of steel, glass-lined with “Blue Glass 4753” flow-coating method at 850°C WRAS (BS6920-1) and KTW-BWGL approved according to UBA specifications (German Environmental Agency)
- Corrosion-proof magnesium anode
- Regulation and safety rod thermostat
- LED heating lamp shows that the heating cycle is in progress
- External casing made of sheet metal coated with epoxy powder paint
- Rigid polyurethane (PU) insulation layer
- IPX4 protective cover on electrical parts
- Stored water temperature indicator



WARRANTY:

- 2 YEARS ON THE TANK AND COMPONENTS

TECHNICAL DATA		SERIES VD 50÷100		
U.M.	VD 50	VD 80	VD 100	
Capacity	l	50	80	100
Code	/	171843	171844	171845
Warranty	yr	2	2	2
Power	kW	1,2	1,2	1,2
Voltage	V~	230	230	230
Heating time (ΔT50 °C)	min.	153	245	306
ErP Energy Class	ErP	C	C	C
ErP Test profile		M	M	L
Max. operating temperature	°C	75	75	75
Max. operating pressure	MPa	0,8	0,8	0,8
Net weight	kg	15,1	21,8	25,5
Hydraulic connections (KW-WW)	G	½"	½"	½"
Dimensional values: A/B	mm	511/288	742/518	893/670

