

Big Size



SERIES VF 150-200

Wall-hung storage water heaters are designed to satisfy the most varied market requirements. The external control knob makes it easy to adjust the water temperature. Also recommended for industrial and collective use.




- Storage tank of steel, glass-lined with “Blue Glass 4753” flow-coating method at 850°C WRAS (BS6920-1) and KTW-BWGL approved according to UBA specifications (German Environmental Agency)
- 88 mm tank inspection flange
- Corrosion-proof magnesium anode
- Screw-in heating element in copper fitted on a flange
- Regulation and safety rod thermostat
- Rigid polyurethane (PU) insulation layer
- External casing made of sheet metal coated with epoxy powder paint
- **IPX4 protective cover over electrical parts**
- Stored water temperature indicator

WARRANTY:

- **5 YEARS ON THE TANK**
- **2 YEARS ON THE OTHER COMPONENTS**



TECHNICAL DATA	U.M.	VF 150	VF 200
Capacity	l	157,6	210,1
Code	/	172418	172419
Warranty	yr	2+3	2+3
Power	kW	2,0	2,0
Voltage	V~	230	230
Heating time ($\Delta T50$ °C)	min.	275	367
ErP Energy Class		C	C
ErP Test profile		L	L
Max. operating temperature	°C	95	95
Max. operating pressure	MPa	0,6 / 1,2	0,6 / 1,2
Net weight	kg	59,6	70,2
Hydraulic connections (KW-WW)	G	3/4" (Rp)	3/4" (Rp)
Dimensional values: A	mm	1026	1297
Dimensional values: B	mm	570	570

